

The RackView Pro/Sun Range

**Rack Mounted KVM drawer range
(with optional KVM switches)**



1U (1.75") KVM drawer

15", 17" or 19" screen versions

Full Sun Keyboard available

All International keyboard options

**Compatible with PC, Unix, Sun and Mac,
plus serial devices (via switch)**



Trackball or touchpad versions

RackView Pro features

Sun keyboard option

All international keyboard layouts available

Single, MultiPoint or matrix KVM switch options

Serial Console server options

Saves 85% of space compared with
conventional upright monitors

Quick and easy to install

Fits rack depths 46cm upwards

Supports most types of computer

Unit discreetly concealed when not in use

Full size keyboard and full numeric keypad

Trackball or touchpad mouse options



The RackView range from Rose offers the most cost-effective and efficient way to control server room hardware and Rack-mounted computers. All RackViews are 1U rack mountable KVM console drawers and include a high resolution LCD Monitor, full sized keyboard (including extra Sun keys) in any international layout, numeric keypad and either touchpad or trackball mouse. A RackView can be placed at any height within a 19" rack offering maximum user comfort and minimum space usage. RackViews are also available in a "split" configuration, allowing the monitor to be mounted at eye-height with the keyboard at a comfortable access height - ideal for cramped access or "walk-up" situations.



Specifications - RackView Pro RVP-515 series

Display Size:	15"
Panel Type:	Active Matrix TFT LCD
Resolution Capabilities:	Up to 1024 X 768 (XG A)
Pixel Pitch:	0.297mm x 0.297mm
Viewing Angle (CR>10):	Horizontal 130° (Typ) Vertical 100° (Typ)
Contrast Ratio:	400:1
Brightness:	White 250cd/m2 (C enter 1 point Typ)
Back Light:	Dual Lamps
Supported Colours:	16M Colours (6-bit with FRC)
Response Time:	5 ms Rising, 11ms Falling
O/S Compatibility:	Dos, Windows (3.1, 9x, 2000, N T 4, M E , XP, 2003 Server) Linux, Novell 3.12-6, HP UX, SUN
Connectors:	PS/2, USB (keyboard & mouse) HD15 (video)
System Cables:	VGA x 1, PS/2 x 2, plus USB for RVP-515-SUN only.
Keyboard/Mouse:	106 key PS/2 keyboard with touch pad, additional Sun function keys
Sync:	45~80K HZ
Power Source:	Auto-sensing 100-240 V.AC input
Power Consumption:	16W , 10.41W for Panel
Operating temperature:	0° ~ 50° C / 32° ~ 122° F
Storage temperature:	-20° ~ 60° C / -4° ~ 140°F
Operating humidity:	10%~90%RH
Unit dimensions:	455x450x44mm / 17.9x17.7x1.7in
Packaged dimensions:	570x600x210mm / 22.4x23.6x8.3in
Net Weight:	11.0K g / 24.2Lb
Packaged Weight:	15.2K g / 33.5Lb
Chassis Construction:	Heavy duty steel
MTBF:	50,000 hours

Keyboard Language: USA , UK , German, French, Spanish, Italian, Portuguese, Dutch,
Swiss, Belgian, Swedish, Norwegian, Danish, Japanese, Taiwanese
Certifications: C E /FC C UL



Specifications – RackView Pro/Sun RVP-517/S series

Display Size: 17"
Panel Type: Active Matrix TFT LCD
Resolution Capabilities: Up to 1280X1024 (SXGA)
Pixel Pitch: 0.264mm x0.264mm
Viewing Angle (CR>10): Horizontal 60~70° (Typ) Vertical 45~60° (Typ)
Contrast Ratio: 450:1
Brightness: White 250cd/m2 (Center 1 point Typ)
Back Light: Four Lamps
Supported Colours: 16.2M Colours (6-bit with FRC)
Response Time: 2ms Rising, 14ms Falling
O/S Compatibility: Dos, Windows (3.1, 9x, 2000, NT4, ME, XP, 2003 Server) Linux,
Novell 3.12-6, HP UX, SUN
System Cables: VGA x 1, PS/2 x 2, plus USB for RVP-515-SUN only.
Keyboard/Mouse: 106 key PS/2 keyboard with touch pad, additional Sun function keys
Sync: 45~80KHZ
Power Source: Auto-sensing 100-240 V.AC input
Power Consumption: 25W , 19.05W for Panel
Operating temperature: 0° ~ 50° C / 32° ~ 122° F
Storage temperature: -20° ~ 60° C / -4° ~ 140°F
Operating humidity: 10%~90%RH
Unit dimensions: 455x450x44mm / 17.9x17.7x1.7in
Packaged Dimensions: 570x600x210mm / 22.4x23.6x8.3in
Net Weight: 11.4Kg / 25.1Lb
Packaged Weight: 16.4Kg / 36.1Lb
Chassis Construction: Heavy duty steel
MTBF: 50,000 hours
Keyboard Language: USA, UK, German, French, Spanish, Italian, Portuguese, Dutch, Swiss
Belgian, Swedish, Norwegian, Danish, Japanese, Taiwanese
Certification: CE/FCC, UL



Specifications – RackView Pro/Trackball series

Display Size:	17"
Panel Type:	Active Matrix TFT LCD
Resolution Capabilities:	Up to 1280X1024 (SXGA)
Pixel Pitch:	0.264mm x0.264mm
Viewing Angle (CR>10):	Horizontal 60~70° (Typ) Vertical 45~60° (Typ)
Contrast Ratio:	450:1
Brightness:	White 250cd/m2 (Center 1 point Typ)
Back Light:	Four Lamps
Supported Colours:	16.2M Colours (6-bit with FRC)
Response Time:	2ms Rising, 14ms Falling
O/S Compatibility:	Dos, Windows (3.1, 9x, 2000, NT4, ME, XP, 2003 Server) Linux, Novell 3.12-6, HP UX, SUN
System Cables:	VGA x 1, PS/2 x 2, plus USB for RVP-515-SUN only.
Keyboard/Mouse:	106 key PS/2 keyboard with inbuilt 2 button trackball.
Sync:	45~80KHZ
Power Source:	Auto-sensing 100-240 V.AC input
Power Consumption:	25W , 19.05W for Panel
Operating temperature:	0° ~ 50° C / 32° ~ 122° F
Storage temperature:	-20° ~ 60° C / -4° ~ 140°F
Operating humidity:	10%~90%RH
Unit dimensions:	455x450x44mm / 17.9x17.7x1.7in
Packaged Dimensions:	570x600x210mm / 22.4x23.6x8.3in
Net Weight:	11.4Kg / 25.1Lb
Packaged Weight:	16.4Kg / 36.1Lb
Chassis Construction:	Heavy duty steel
MTBF:	50,000 hours
Keyboard Language:	USA, UK, German, French, Spanish, Italian, Portuguese, Dutch, Swiss Belgian, Swedish, Norwegian, Danish, Japanese, Taiwanese
Certification:	CE/FCC, UL

RackView Pro/Sun sets new standards in the KVM drawer market, with its full Sun keyboard layout and “split height” installation options.